

Kidde ProLine™

Carbon Dioxide



PRO 5 CD

- ◆ Clean Agent Leaves No Residue
- ◆ Protect Audio Storage, Video Storage Areas
- ◆ Seamless Aluminum Cylinder: No Welds, No Leaks



PRO 10 CD

- ◆ Clean Agent Leaves No Residue
- ◆ Protect Data Processing Centers, Laboratories
- ◆ Alternative to Halon 1211



PRO 15 CD

- ◆ Clean Agent Leaves No Residue
- ◆ Ideal for Food Storage and Processing Plants
- ◆ For Areas Where Contamination is a Concern



PRO 20 CD

- ◆ Clean Agent Leaves No Residue
- ◆ Protect Manufacturing Equipment
- ◆ Ideal Where Clean Up Time is an Important Factor

CO2 Fire Extinguisher Features

- Long lasting nickel/chrome plated brass valve with stainless steel handle and lever
- Alternate clean agent for Halon 1211 applications
- Agent will not contaminate food, valuable materials or electronics.
- Environmentally safe.
- CO2 gas dissipates quickly, leaving no residue.
- Seamless aluminum cylinder is strong but lightweight for easy handling.
- Durable epoxy paint finish resists chipping
- Mar-resistant pictogram mylar label.
- 5-Year Warranty

Approvals and Listings

ANSI/UL (Underwriters Laboratories Inc.)
 DOT (Department of Transportation)
 OSHA (Occupational Safety and Health Administration)
 USCG (United States Coast Guard)

Pro Line Carbon Dioxide

	5-B:C	10-B:C	10-B:C	10-B:C
UL Rating	5-B:C	10-B:C	10-B:C	10-B:C
Agent	CO2	CO2	CO2	CO2
Model	PRO 5 CD	PRO 10 CD	PRO 15 CD	PRO 20 CD
Part No.	466180	466181	466182	466183
Contents (lb/kg)	5.0/2.27	10.0/4.54	15.0/6.8	20.0/9.07
Shipping (lb/kg)	15.0/6.8	30.0/13.6	40.0/18.1	51.0/23.10
Diameter (in/cm)	5.25/13.34	6.87/17.46	6.87/17.46	8.0/20.32
Height (in/cm)	17.0/43.2	19.37/49.2	26.0/66.0	26.0/66.0
Width (in/cm)	8.5/21.6	10.87/27.6	10.87/27.6	12.0/30.5
Discharge Time (sec)	7-9	8-10	12-14	15-17
Discharge Range (ft)	3-8	3-8	3-8	3-8
Operating Pressure (PSI)	850	850	850	850
Cylinder Material	Aluminum	Aluminum	Aluminum	Aluminum
Valve Material	Brass	Brass	Brass	Brass
Bracket Provided	Wall	Wall	Wall	Wall
USG Approval	Yes	Yes	Yes	No

Operable Temperature Range All Models: -40F to 120F (-40 C to 48C)

Brackets: Units shipped with a heavy duty hanger for wall or flat surface mounting. The hanger is universal and fits most CO2 extinguisher designs. USCG and DOT vehicle brackets are available as an option.