

# Kidde Wheeled

## Tri-Class Dry Chemical (ABC)



### PROPLUS 50 MP

- ◆ Ready to Use Stored Pressure
- ◆ One Person Operation



### PROPLUS 150 MP

- ◆ Ready to Use Stored Pressure
- ◆ One Person Operation



### PROPLUS 150 MP-C

- ◆ Cartridge Operated for Remote Areas
- ◆ 36" Steel Spokes with Hard Rubber Tires for Rougher Terrain
- ◆ One Person Operation

Wheeled Units Tri-Class Dry Chemical

MODEL NO.	ProPlus 50 MP	ProPlus 150 MP	ProPlus 150 MP-C
CAPACITY LBS. (KG.)	50 (22.60)	125 (56.70)	145 (65.77)
UL RATING	30-A:160-B:C	40-A:240-B:C	40-A:240-B:C
AGENT	ABC	ABC	ABC
PART NUMBER	466504	466507	466510
VALVE MATERIAL	BRASS	BRASS	BRASS
SHELL MATERIAL	STEEL	STEEL	STEEL
SHIPPING WT. LBS. (KG.)	140 (63.00)	300 (135.00)	435 (196.75)
OPERATING PRESSURE	240	240	225
TEMP RANGE (F)	-40 TO 120°	-40 TO 120°	-40 TO 120°
DISCHARGE TIME (SEC.)	36	45	43
RANGE FEET (METERS)	25-35 (7.6-10.6)	30-40 (9.1-12.2)	25-35 (7.62-10.67)
UNIT HEIGHT IN. (CM.)	46.25 (117.5)	58 (147.3)	52 (132.08)
UNIT WIDTH IN. (CM.)	23 (58.4)	28 (71.1)	27 (68.58)
SHELL DIAMETER IN. (CM.)	28.75 (72.98)	44.5 (112.96)	38.75 (98.36)

Operable Temperature Range All Models:  
-40F to 120F (-40C to 48C)

### Wheeled Multi-Purpose Units

#### Features:

- Wide variety of types and sizes to meet market requirements
- Rugged industrial designs
- Convenient wheeled design for mobility and flexibility
- Durable chrome plated valves with easy to operate lever for quick discharge open and shut off
- Heavy duty steel cylinders with chip resistant finish
- Flexible hose and long discharge range to protect operator from heat, smoke and flames

#### Typical Applications

Where chemical and petroleum products are stored or in use: warehouses and stockrooms, construction sites, manufacturing plants, auto repair shops, marinas, parking garages and high hazard areas

#### Approvals and Listings

ANSI/UL (Underwriters Laboratories Inc.)  
DOT (Department of Transportation)  
NFPA 10 Recognized  
USCG (United States Coast Guard)