

Kidde Pro Line™

Multi-Purpose Dry Chemical (ABC)



PRO2.5 MP

- ◆ Ideal for Vehicles, Apartments and Trailers
- ◆ Standard Commercial Design
- ◆ Compact Design



PRO4 MP PRO5 MP

- ◆ 4lb. Model Meets 2-A:10-B:C Compliance
- ◆ 5lb. Model Exceeds 2-A:10-B:C Compliance
- ◆ Ideal for Common Industrial Use: Office, Hotels, Schools.



PRO10 MP

- ◆ Ideal for Industrial Applications such as Hospitals, Universities, Warehouse and Plant Locations.
- ◆ Commercial Design Meets Industrial Requirements.
- ◆ Seamless Steel Cylinder is Superior to Welded Designs.



PRO20 MP

- ◆ Designed for High Hazard Industrial Application.
- ◆ Highest UL Rating For Multi Purpose Models.
- ◆ Seamless Steel Cylinder is Superior to Welded Designs

ProLine Multi-Purpose Dry Chemical

| UL Rating | 1-A:10-B:C | 2-A:10-B:C | 3-A:40-B:C | 4-A:60-B:C | 10-A:80-B:C |
|--|-------------|-------------|-------------|-------------|-------------|
| Effective Against Class | ABC | ABC | ABC | ABC | ABC |
| Model | PRO2.5 MP | PRO4 MP | PRO5 MP | PRO10 MP | PRO20 MP |
| Part No. | 466227 | 466268 | 466112 | 466204 | 466206 |
| Contents (lb/kg) | 2.50/1.20 | 4.00/1.82 | 5.00/2.30 | 10.00/4.50 | 18.00/8.20 |
| Filled (lb/kg) | 3.90/1.80 | 8.38/3.80 | 7.90/3.60 | 17.00/7.70 | 30.00/13.60 |
| Shipping (lb/kg) | 4.20/1.90 | 8.80/4.00 | 8.50/13.90 | 19.50/8.80 | 30.44/13.83 |
| Diameter (in/cm) | 3.30/8.30 | 4.50/11.43 | 4.50/11.40 | 5.12/13.00 | 7.00/17.80 |
| Height (in/cm) | 15.00/38.10 | 16.00/40.64 | 16.00/40.60 | 21.18/53.80 | 21.60/54.90 |
| Width (in/cm) | 5.30/13.50 | 7.80/19.81 | 7.80/19.70 | 8.22/20.90 | 8.30/21.10 |
| Discharge Time (sec) | 8-10 | 8-10 | 13-15 | 19-21 | 19-22 |
| Discharge Range (ft) | 6 | 12 | 18 | 20 | 20 |
| Optional Metal Strap Bracket Part Number | 466401 | 466400 | 466400 | 366242 | 292474 |
| Operating Pressure (PSI) | 100 | 100 | 195 | 195 | 195 |
| Cylinder Material | Aluminum | Aluminum | Aluminum | Steel | Steel |
| Units/Overpack | 6 | 4 | 4 | 1 | 1 |
| Bracket Provided | Wall Hanger | Wall Hook | Wall Hook | Wall Hook | Wall Hook |

Operable Temperature Range All Models: -40F to 120F (-40C to 48C)

Brackets: Units are equipped with a wall hanger for mounting in standard applications. Heavy duty vehicle brackets are available for high traffic and vibration areas as well as U.S. Coast Guard, Bureau of Motor Carrier Approvals.

Pro Line Multi-Purpose Dry Chemical Features

- Strong aluminum valve body for standard commercial applications.
- Designed to meet most commercial and industrial specifications.
- Seamless aluminum and steel cylinders have chip resistant epoxy finish.
- Reliable pressure gauge for fast and easy pressure checks.
- Superior agent provides higher UL ratings than other agents in comparable sizes
- Handle made from pressed heavy gauge metal for added strength.
- Fits all standard cabinets.
- Mar-resistant pictogram mylar label.
- Six Year Warranty

Approvals and Listings

ANSI/UL (Underwriters Laboratories Inc.)
 DOT (Department of Transportation)
 OSHA (Occupational Safety and Health Administration)
 USCG (United States Coast Guard)
 BMC (Bureau of Motor Carrier Safety Regs. Pat. 393.95)